



FEATURES

- Complementary to BC856/BC857/BC858
- Power Dissipation of 200mW
- Ideally suited for automatic insertion
- For switching and AF amplifier applications



MECHANICAL DATA

- Small Outline Plastic Package
- Epoxy UL: 94V-0
- Mounting position: Any



APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)


Parameter	Symbol	BC846		BC847			BC848			Unit
Marking		BC846A	BC846B	BC847A	BC847B	BC847C	BC848A	BC848B	BC848C	
		1A	1B	1E	1F	1G	1J	1K	1L	
Collector-Base Voltage	V _{CBO}	80		50			30			V
Collector-Emitter Voltage	V _{CEO}	65		45			30			V
Emitter-Base Voltage	V _{EBO}	6								V
Collector Current-Continuous	I _C	100								mA
Collector Power Dissipation	P _C	200								mW
Thermal resistance From junction to ambient	R _{θJA}	625								°C/W
Junction Temperature	T _J	150								°C
Storage Temperature	T _{STG}	-55~+150								°C

ELECTRICAL CHARACTERISTICS (T_A=25°C)


Parameter	Symbol	Test Conditions		Min.	Typ.	Max.	Unit
Collector-base breakdown voltage	V _{(BR)CBO}	BC846	I _C =10μA, I _E =0	80			V
		BC847		50			
		BC848		30			
Collector-emitter breakdown voltage	V _{(BR)CEO}	BC846	I _C =10mA, I _B =0	65			V
		BC847		45			
		BC848		30			
Emitter-base breakdown voltage	V _{(BR)EBO}	I _E =10μA, I _C =0		6			V
Collector cut-off current	I _{CBO}	BC846	V _{CB} = 70V, I _E =0			100	nA
		BC847	V _{CB} = 50V, I _E =0				
		BC848	V _{CB} = 30V, I _E =0				
Collector cut-off current	I _{CEO}	BC846	V _{CE} = 60V, I _B =0			100	nA
		BC847	V _{CE} = 45V, I _B =0				
		BC848	V _{CE} = 30V, I _B =0				
DC current gain	h _{FE}	BC846A; BC847A;BC848A	V _{CE} = 5V, I _C =2mA	110		220	
		BC846B; BC847B;BC848B		200		450	
		BC847C; BC848C		420		800	
Collector-emitter saturation voltage	V _{CE(sat)}	I _C =100mA, I _B =5mA				0.50	V
Base -emitter saturation voltage	V _{BE(sat)}	I _C =100mA, I _B =5mA				1.10	V
Transition frequency	f _T	V _{CE} =5V, I _C =10mA, f=100MHz		100			MHz
Collector output capacitance	Cob	V _{CB} =10V, f=1MHz				4.5	pF
Emitter cut-off current	I _{EBO}	V _{EB} =5V, I _C =0V				100	nA

TYPICAL CHARACTERISTICS


Static Characteristic




h_{FE} — I_C







$V_{CE sat}$ — I_C




$V_{BE sat}$ — I_C






SOT-23 PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.80	3.05	0.110	0.120
B	1.20	1.40	0.047	0.055
C	0.90	1.15	0.035	0.045
D	0.37	0.50	0.015	0.020
G	1.75	2.05	0.069	0.081
H	0.01	0.100	0.001	0.004
J	0.085	0.180	0.003	0.007
K	0.35	0.69	0.014	0.029
L	0.89	1.02	0.035	0.040
S	2.10	2.65	0.083	0.104
V	0.45	0.60	0.018	0.024

RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.71	0.97	0.028	0.038
B	1.88	2.13	0.074	0.084
C	0.71	0.97	0.028	0.038
D	0.81	1.07	0.032	0.042

ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
BC846-BC848	SOT-23	3000PCS	7"

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.