

FEATURES

- | I(hold): 0.1A~14A
- | RoHS compliant Lead-Free
- | Fast time-to-trip
- | Low resistance
- | Radial leaded devices



APPLICATIONS

- | PC motherboard - plug and play protection
- | Industrial control
- | Automotive electronics
- | Medical products
- | Power ports

ENVIRONMENTAL SPECIFICATIONS

Test	Conditions	Resistance change
Passive aging	+85°C, 1000 hours	$\leq R_{\max}$
Humidity aging	+85°C, 85%R.H., 1000 hours	$\leq R_{\max}$
Thermal shock	+125°C to -55°C, 10 times	$\geq R_{\min}$
Resistance to solvent	MIL-STD-202, Method 215	No change
Vibration	MIL-STD-202, Method 201	No change
Ambient operating conditions : - 40°C to +85°C Maximum surface temperature of the device in the tripped state is 125 °C		

PERFORMANCE SPECIFICATION

Type Number	I_{hold}	I_{trip}	V_{max}	I_{max}	$P_{d\ typ}$	Max. Time to Trip		Ri_{min}	Ri_{max}
	A	A	$V_{(DC)}$	A	W	Current A	Tmax S	mΩ	mΩ
SK16-010	0.1	0.3	16	100	0.38	0.5	5	1500	7500
SK16-025	0.25	0.5	16	100	0.45	1.25	5	500	1950
SK16-030	0.3	0.6	16	100	0.49	1.5	5	300	700
SK16-050	0.5	1.0	16	100	0.56	2.5	5	200	500
SK16-075	0.75	1.5	16	100	0.72	3.75	5	100	320
SK16-090	0.9	1.8	16	100	0.83	4.5	5	90	180
SK16-110	1.1	2.2	16	100	0.94	5.5	5	60	150
SK16-135	1.35	2.7	16	100	1.2	6.75	5	40	130
SK16-160	1.6	3.2	16	100	1.4	8	5	40	110
SK16-200	2	4	16	100	2.2	6	15	35	75
SK16-300	3	6	16	100	2.3	9	15	20	60
SK16-400	4	8	16	100	2.4	12	15	20	40
SK16-500	5	10	16	100	2.6	15	15	14	25
SK16-600	6	12	16	100	2.8	18	15	10	21
SK16-700	7	14	16	100	3.0	21	15	8	15
SK16-800	8	16	16	100	3.0	24	15	6	13
SK16-900	9	18	16	100	3.3	27	25	4	12
SK16-1000	10	20	16	100	3.7	30	30	4	11
SK16-1100	11	22	16	100	3.7	33	30	3	9
SK16-1200	12	24	16	100	4.2	36	30	3	8
SK16-1300	13	26	16	100	4.2	39	50	3	8
SK16-1400	14	28	16	100	4.2	40	50	3	7

V_{max} = Maximum operating voltage device can withstand without damage at rated current (I_{max}).

I_{max} = Maximum fault current device can withstand without damage at rated voltage (V_{max}).


I_{hold} = Hold Current. Maximum current device will not trip in 25°C still air.

I_{trip} = Trip Current. Minimum current at which the device will always trip in 25°C still air.

P_d = Power dissipation when device is in the tripped state in 25°C still air environment at rated voltage.

$Ri_{min/max}$ = Minimum/Maximum device resistance prior to tripping at 25°C.

DIMENSIONS




Part Number	A(max.)	B(max.)	C(max.)	D	E(Min.)	F(mm)	TYPE
SK16-010	5.5	12.0	3.0	5.1±0.75	4.6	Φ0.5	TYPE 1
SK16-025	5.5	12.0	3.0	5.1±0.75	4.6	Φ0.5	TYPE 1
SK16-030	5.5	12.0	3.0	5.1±0.75	4.6	Φ0.5	TYPE 1
SK16-050	5.5	12.0	3.0	5.1±0.75	4.6	Φ0.5	TYPE 1
SK16-075	5.5	13.5	3.0	5.1±0.75	4.6	Φ0.5	TYPE 1
SK16-090	7.4	13.5	3.0	5.1±0.75	4.6	Φ0.5	TYPE 1
SK16-110	7.4	13.5	3.0	5.1±0.75	4.6	Φ0.5	TYPE 1
SK16-135	7.4	13.5	3.0	5.1±0.75	4.6	Φ0.5	TYPE 1
SK16-160	7.4	14.0	3.0	5.1±0.75	4.6	Φ0.5	TYPE 1
SK16-200	9.0	12.0	3.0	5.1±0.75	4.6	Φ0.5	TYPE 2
SK16-300	9.0	12.0	3.0	5.1±0.75	4.6	Φ0.8	TYPE 2
SK16-400	10.0	13.0	3.0	5.1±0.75	4.6	Φ0.8	TYPE 2
SK16-500	11.8	17.5	3.0	5.1±0.75	4.6	Φ0.8	TYPE 2
SK16-600	11.8	17.5	3.0	5.1±0.75	4.6	Φ0.8	TYPE 2
SK16-700	13.5	23.0	3.0	5.1±0.75	4.6	Φ0.8	TYPE 2
SK16-800	13.5	23.0	3.0	5.1±0.75	4.6	Φ0.8	TYPE 2
SK16-900	15.0	24.0	3.0	5.1±0.75	4.6	Φ0.8	TYPE 2
SK16-1000	18.0	26.0	3.0	5.1±0.75	4.6	Φ0.8	TYPE 2
SK16-1100	18.0	26.0	3.0	5.1±0.75	4.6	Φ0.8	TYPE 2
SK16-1200	22.5	26.0	3.0	10.2±0.75	4.6	Φ0.8	TYPE 2
SK16-1300	24.0	30.0	3.0	10.2±0.75	4.6	Φ0.8	TYPE 2
SK16-1400	24.0	30.0	3.0	10.2±0.75	4.6	Φ0.8	TYPE 2

THERMAL DERATING CHART-IH(A)

Part Number	Ambient Operation Temperature									
	-40 °C	-20 °C	0 °C	25 °C	30 °C	40 °C	50 °C	60 °C	70 °C	85 °C
SK16 Series	137%	130%	115%	100%	91%	83%	77%	68%	61%	52%

WAVE SOLDERING



Wave Parameter		Lead-free assembly
Pre Heat	Temperature Min	100°C
	Temperature Max	150°C
	Time(min to max)	60 – 180 secs
Solder pot Temperature		280°C Max
Solder Dwell Time		2-5 seconds

ORDERING INFORMATION

Part Number	Base Quantity	Packing Option
SK16-010~SK16-600	1000pcs	Bag
SK16-700~SK16-900	500pcs	Bag
SK16-1000~SK16-1400	200pcs	Bag

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.