



FEATURES

- | The Plastic Package Carries Underwriters Laboratory Flammability Classification 94V-0
- | Guardring For Overvoltage Protection
- | Low Reverse Leakage
- | High Forward Surge Current Capability



DO-201



Schematic Symbol

APPLICATIONS

- | Case : Molded Plastic Body
- | Polarity : Polarity Symbol Marking On Body
- | Mounting Position : Any

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

Parameter	Symbol	Value	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	40	V
Maximum RMS Voltage	$V_{R(RMS)}$	28	V
Maximum DC Blocking Voltage	V_{DC}	40	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	5.0	A
Non-repetitive Peak Forward Surge Current 8.3 ms Singlehalf Sine-Wave	I_{FSM}	125	A
Maximum Forward Voltage @ $I_F=5.0\text{A}$	V_F	0.45	V
Typical Thermal Resistance (Note 1)	$R_{\theta JA}$	54	$^{\circ}\text{C/W}$
Maximum Reverse Current @ V_{DC}	I_R	0.1	mA
		20	mA
Type Junction Capacitance $V_R=4.0\text{V}, f=1\text{MHz}$	C_J	320	pF
Operating Junction Temperature	T_J	-55 to +125	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150	$^{\circ}\text{C}$

Note:1) Thermal resistance from junction to ambient at 0.375" (9.5 mm) lead length, PCB mounted.

CHARACTERISTIC CURVES

Fig. 1- Typical Forward Characteristic




Fig. 2-Forward Current Derating Curve




Fig. 3-Maximum Non Repetitive Peak Forward Surge Current






Fig. 4-Typical Reverse Characteristics




WAVE SOLDERING



Wave Parameter		Lead-free assembly
Pre Heat	Temperature Min	100°C
	Temperature Max	150°C
	Time(min to max)	60 – 180 secs
Solder pot Temperature		280°C Max
Solder Dwell Time		2-5 seconds

DO-201 PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	8.50	9.50	0.335	0.375
B	4.80	5.60	0.189	0.220
C	1.10	1.45	0.043	0.057
D	24.00	-	0.945	-

ORDERING INFORMATION

Part Number	Marking	Component Package	Per Carton	Description
TSR540L	TSR540L	DO-201	1250pcs	Reel

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware' s global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.